


## Material overview


Item-No.	Temperature-resistant up to *	Antistatic	Slipping	Oil-resistant	Abrasion-proof	FDA-licensed
FM100.001	100 °C		✓			
FM100.002	70 °C			✓	✓	
FM100.003	70 °C			✓	✓	
FM100.004	Coating: 180 °C Textile: 300 °C				✓	
FM100.005	90 °C		✓		✓	✓
FM100.006	90 °C		✓		✓	
FM100.007	70 °C					
FM100.008	150 °C					✓
FM100.009	Coating: 315 °C Textile: 500 °C		✓		✓	
FM100.010	90 °C	✓	✓		✓	

\* These temperature indications are valid for permanent load. Short term higher loads are possible.

### Material for collecting funnels and chutes:



Mat.-no.:  
FM100.001  
(PE, blue)



Mat.-no.:  
FM100.002  
(PVC, silver)



Mat.-no.:  
FM100.003  
(PVC, blue)



Mat.-no.:  
FM100.004  
(Kevlar,  
silver/yellow)




Mat.-no.:  
FM100.005  
(PP, white,  
FDA)



Mat.-no.:  
FM100.006  
(PBT, white)


### Material for side protection curtain RS:




Mat.-no.:  
FM100.009  
(PTFE, grey)



Mat.-no.:  
FM100.010  
(PP, white,  
antistatic)



Mat.-no.:  
FM100.007  
(PVDC,  
anthracite)



Mat.-no.:  
FM100.008  
(PET, white,  
FDA)